



**EUROTRAMP®**

## Instruction for the EUROTRAMP Ground trampoline

1. Please dig the pit as suggested in the attached technical drawing for ground trampoline. We recommend if the ground is not very stable to fix the walls with concrete or stone plates. The rectangular steel tubes can alternatively be put on the ground or integrated in a concrete base; the dimensions of the steel frame are 12 cm wide and 6 cm high.
2. The mounting starts by putting together the frame parts. Please take into account that the three hooks in the corners for mounting the frame pads must be on the upper side. The longer parts of the frame should be combined with the underground.



3. The mounting of the jumping bed should be started by fixing 2 steel springs in each corner



**EUROTRAMP®**



4. Then 2 persons should fix 2 oppositely placed steel springs and go on like this until all springs are mounted.



5. The mounting of the smaller frame pads has to be done by fixing the frame pads with screws at the outside of the frame



**EUROTRAMP®**



6. Please fix the frame pads as shown in the following picture by attaching 3 steel springs at the three hooks on the inner side of the frame





**EUROTRAMP®**

7. Then fix the length side frame pads with screws at the outside of the length parts of the frame



8. Use the black rubber cable and fix its hook at the screw of the frame padding

### **Never fix the frame pads at the jumping bed**

If the trampoline will not be used for a longer time we recommend to dismount the frame pads, steel springs and jumping bed and to store it dry and sun protected. This helps to let it live longer.



**EUROTRAMP®**

## Parts list for the EUROTRAMP Ground Trampoline

<u>Article description</u>	<u>Quantity</u>
Frame parts 464 cm long, rectangular tube 120x60x3 mm, hot dip galvanized	2
Frame parts 281 cm long, rectangular tube 120x60x3 mm, hot dip galvanized	2
Hot dip galvanized Steel springs 30 x 235 mm,	100
Jumping bed 366 x 183 cm, PVC-coated fro ground trampolines	1
Coverall frame pads for length side each with 6 steel springs and 3 screws and plates	2
Coverall frame pads for forehead side each with 6 steel springs and 3 screws and plates	2
Information plate yellow 420 x 297 mm Using instruction for the Ground trampoline	1